Inventor: Asim H. Abbasi (H): 919-463-0617 (C): 919-244-7351

(1)




FIGURE 1: Hardware setup of the voice activated wireless control system. The wireless communication of single transmitter with multiple receiver units is based on a protocol.

TITLE: System and method for voice commands recognition and controlling devices wirelessly using protocol based communication

Inventor: Asim H. Abbasi (H): 919-463-0617 (C): 919-244-7351

(2)




FIGURE 2: Extending the Network to complete home. Audio transmitter/receiver will work based on AM/FM technique whereas Digital transmitter/receiver will work based on ASK/FSK technique.

Inventor: Asim H. Abbasi (H): 919-463-0617 (C): 919-244-7351

(3)




FIGURE 3: Digital Receiver Module schematic, shown attached with Electric bulb to be controlled.

Inventor: Asim H. Abbasi (H): 919-463-0617 (C): 919-244-7351

(4)


A.


	Network_ID	Device_ID	Command
В.	0011	11100011	0001


FIGURE 4: The architecture of protocol used in the wireless communication of single transmitter with multiple receiver units attached with each device to be controlled.


Inventor: Asim H. Abbasi (H): 919-463-0617 (C): 919-244-7351

(5)












FIGURE 5: Working of Microcontroller to implement Protocol